

Max Working Height (m)	17.70
Max Platform Height (m)	15.70
Max Horizontal Working Outreach (m)	9.30
Max Horizontal Outreach to edge of basket (m)	8.80
Lift Capacity / SWL (kg)	200
Weight / Outreach Limited (Yes/No)	Yes
Turret Rotation	360°
Basket Rotation	140°
Length with basket (m)	5.10
Length w/out basket (m)	4.25
Width stowed tracks (m)	0.78
Height (m) stowed	1.95
Basket Dimensions	1.2 x .66
Total Weight (kg)	2457
Max ground pressure driving (approx)	47 kN/m ²
Max stabilizer force	15 kN
Max stabilizer pressure with std foot pad	478kN/m ²
Gradeability length-wise	51% / 27 degrees
Gradeability sideways	27% / 15 degrees
Stabilizer set-up dimensions	3.9 x 3.3 o/o
Narrow set-up dimensions	N/A
Max slope for stabilizers	14 degrees
Standard Power Source/s	Honda 13 Hp Petrol & 240 Volt electric system
Optional Power Sources	Yanmar 9 hp or Kubota 14 hp Diesel
Drive system	Tracks
Expanding tracks	Std
Drive speed km/h	1.5
2 Speed Drive	No
Remote drive control	Radio Option
Battery voltage	12
Basket load control	Std
Electric & Air outlets in basket	Std
Electric emergency lowering	Option

Complies with AS1418.10

(E & OE.)

SPECIFICATIONS

